# DRINKING WATER QUALITY REPOR



**Bolton Point is providing this Drinking Water Quality Report to our consumers** because we want you to be fully formed about your water's quality and the need to protect its source.

This overview of last year's water quality includes details about where your water comes from, what it contains, and how it compares to State standards. If you have any questions about this report or your drinking water, please contact Glenn Ratajczak, Production Manager, 277-0660, ext. 241, gratajczak@ boltonpoint.org, or you may attend any of our regularly scheduled public meetings.

### **TABLE OF CONTENTS**

- A. Water Treatment Processes
- B. Health Effects and Individuals At-Risk
- C. Water Quality Data
- D. General Water Information (Tables 1 & 2)
- E. Detected Contaminants (Tables 3)
- F. Non-detected Contaminants (Table 4)
- G. Major Modifications Completed
- H. Future Projects and Capital **Improvements**
- I. Water Conservation Measures
- J. Security Concerns
- K. Source Water Protection
- L. Lead Service Line Inventory

### LOCATION AND DESCRIPTION OF WATER SERVICES COMMON WATER QUALITY DEFINITIONS

### Bolton Point Municipal Water System (Bolton Point or BP-MWS) ALKALINITY is a measure of the capability of water to

Cayuga Lake is the source of water for the BP-MWS. The water intake is approximately 3 miles north of Stewart Park, 400 feet out from the shore of Cayuga Lake, and 65 feet below the surface HARDNESS is a measure of the calcium and magnesiof the lake. During 2024, the Bolton Point system did not experience any restriction of its water source. The system serves residents of the Towns of Dryden, Ithaca and Lansing, and the Villages of Cayuga Heights and Lansing, and provides water to some City of Ithaca customers on Oakwood Lane, Hector Street, Warren Place, Sunrise Road, and Richards Place. It provides water to other parts of the City of Ithaca and Cornell during emergencies and planned maintenance periods. Meetings of the Bolton Point Water Commission are held on the first Thursday after the first Tuesday of each month at 4:00 p.m. at the Bolton Point water treatment plant, 1402 East Shore Drive, Ithaca New York, 14850.

neutralize acids. Bicarbonates, carbonates, and hydroxides are the most common forms of alkalinity.

um content of natural waters. The harder the water, the greater the tendency to precipitate soap and to form mineral deposits. Alkalinity and hardness occur naturally due to the contact of water with minerals in the earth's crust.

**pH** indicates how acidic or alkaline a water sample is. A value of 7 is neutral, 0-6 is acidic and 8-14 is alkaline.

TOTAL ORGANIC CARBON (TOC) is a measure of the organic content of water. A high concentration of TOC in water may lead to high levels of disinfection byproducts.

**TURBIDITY** is a measure of the cloudiness of water. It is an indication of the effectiveness of water treatment. NYS regulations require that treated water turbidity always be below 1 NTU (nephelometric turbidity unit). For filtered systems 95% of the composite effluent samples must be below 0.3 NTU.

### **A. Water Treatment Process**

Bolton Point uses the following conventional surface water treatment.

PRE-TREATMENT: Coagulating agents such as alum or polymers are added to the water to remove impurities and control taste and odor. A disinfectant is added to destroy microorganisms.

MIXING: The water is rapidly mixed to distribute the treatment chemicals evenly.

COAGULATION AND FLOCCULATION: The water flows into large basins where the coagulants react with impurities in the water (coagulation) causing them to form larger, heavier particles called floc (flocculation).

SEDIMENTATION: Flocculated water flows into basins where the floc particles settle to the bottom, thereby removing impurities and chemicals from the water.

FILTRATION: Following the settling process, water flows through layers of anthracite coal, sand, and garnet where further removal of particulate impurities occurs.

POST-TREATMENT: Chlorine is added to inhibit bacterial growth in the distribution system, and the pH is adjusted to inhibit the corrosion of metal pipes and fixtures.

### B. Health Effects and Individuals At-Risk

All drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate the water poses a health risk.

Some people may be more vulnerable to disease causing microorganisms or pathogens in drinking water than the general population. Immuno-compromised persons such as those with cancer undergoing chemotherapy, those who have undergone organ transplants, those with HIV/ AIDS or other immune system disorders, some elderly, and some infants can be particularly at risk from infections. These people should seek advice from their health care provider about their drinking water.

Environmental Protection Agency/ Center for Disease Control (EPA/CDC) guidelines on appropriate means to lessen the risk of infection by cryptosporidium, giardia, and other microbial pathogens are available from the Safe Drinking Water Hotline (800-426-4791). No trace of either of these pathogens has been detected in previous testing of the treated water of Bolton Point. Individuals who think they may have one of these illnesses should contact their health care provider immediately. For additional information please contact Tompkins County Whole Health, 55 Brown Road, Ithaca, New York 14850 or by phone at 274-6688.

### C. Water Quality Data

INTRODUCTION: The sources of drinking water (tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through ground, it dissolves naturally occurring minerals and, in some cases, radioactive material. It also can pick up substances resulting from the presence of animals or from human activities. Contaminants that may be present in source water include microbial contaminants, inorganic contaminants, pesticides and herbicides, organic chemical contaminants, and radioactive contaminants.

To ensure that tap water is safe to drink, the State and the EPA prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. State Health Department and Federal Drug Administration regulations also establish limits for contaminants in bottled water, which must provide the same protection for public health.

In accordance with State regulations, Bolton Point routinely monitors your drinking water for numerous contaminants. Table 3 shows the analytical test results for contaminants that were detected. These results are compared to the applicable State guideline or maximum contaminate level (MCL). Table 4 shows the contaminants that were not detected in your water.

The State allows testing less frequently than once per year for some contaminants since the concentrations of these contaminants do not change frequently. Therefore some data, though representative, are more than one year old.

**TOTAL COLIFORMS**: Coliforms are bacteria that are naturally present in the environment and are used as an indicator that other, potentially harmful, bacteria may be present.

**LEAD AND COPPER**: Bolton Point was required to sample for lead in 2023. There were no violations of State standards.

**SODIUM**: People who are on severely restricted sodium diets should not drink water containing more than 20 mg/L of sodium. Since the 2024 level of sodium in Bolton Point was 34 mg/L, customers on severely restricted sodium diets might wish to consult their health care providers. People who are on moderately restricted sodium diets should not drink water containing more than 270 mg/L of sodium. The sodium levels of the water from Bolton Point are well below this level.

### **D. General Water Information**

Table 1: General Water Data -2024

WATER SYSTEM	BP-MWS	
PUBLIC WATER SUPPLY ID #	5404423	
Water Source	Cayuga Lake	
Approximate population served	30,000	
Number of service connections	7327	
Total production (MG <sup>1</sup> )	876	
Average daily withdrawal (MGD <sup>2</sup> )	2.406	
Average daily delivered (MGD)	2.395	
Average daily lost (MGD)	0.011	
Annual charge per 1000 gal.	\$10.41 <sup>3</sup>	

<sup>&</sup>lt;sup>1</sup>MG = million gallons

During the course of the year, for maintenance purposes, or for emergency help, potable water is exchanged among the three local water systems. If you wish to know if this occurred, the time periods, and the water volumes, please contact Glenn Ratajczak at 277-0660 ext 241.

Required testing by the EPA for the Unregulated Contaminant Monitoring Rule #5 (UCMR5) was completed by Bolton Point in 2024. Information about the rule and the contaminants can be found on EPA website (epa.gov). The results of detected contaminants of UCMR5 can be found in Table 3. For more information on UCMR5 testing contact Glenn Ratajczak at 277-0660 ext 241.

HYDRILLA TREATMENT INFORMATION: Cayuga Lake was treated in 2024 with herbicides after the invasive species Hydrilla was located in Cayuga Inlet in 2011. All monitoring results for sampling related to the Hydrilla Eradication Program can be found at https://tompkinscountyny.gov/health/hydrilla#monitoring

Table 2: General Water Quality Data - 2024

ANALYTE	UNITS	BP-MWS
pH (EP) <sup>1</sup>		8.3
Turbidity (EP)	NTU	0.035
Total Hardness	mg/L	150.0
Total Alkalinity	mg/L	109
Chlorine Residual (EP)	mg/L	1.57
Chlorine Residual (POU) <sup>2</sup>	mg/L	0.55
Turbidity (POU)	NTU	0.051
Total Organic Carbon (EP)	mg/L	2.0
Dissolved Organic Carbon (EP)	mg/L	1.9

<sup>&</sup>lt;sup>1</sup>EP = Entry Point; <sup>2</sup>POU = Point of Use | Definitions of

NTU and mg/L found with Table 3.

<sup>&</sup>lt;sup>2</sup>MGD = million gallons per day

<sup>&</sup>lt;sup>3</sup>Average of the rates charged by the five member municipalities of the BP-MWS.

### **Tables of Detected Contaminants**

Table 3: Detected Contaminants: Bolton Point Municipal Water System

Contaminant	Units	Violation Y/N	Date of Sample	Maximum or average Level Detected (Range)	Regulatory Limit	MCLG or MRDLG	Likely Source of Contamination
Microbiological contan	ninants						
Total Coliform	N/A	No	6/26/24	1 positive sample	TT = 2 or more positive samples within one month.	N/A	Naturally present in the environment.
Turbidity (EP)	NTU	No	11/8/24	0.055	TT=<1 NTU	N/A	Soil runoff.
Turbidity samples(EP)	% be- low MCL	No	Daily	100%	TT=95% of sam- ples <0.3NTU	N/A	Soil runoff.
Turbidity (POU)	NTU	No	8/24	0.069 <sup>5</sup>	MCL>5NTU	N/A	Soil runoff.
Disinfection and Disinf	ection By	-Products					
Total Organic Carbon	mg/L	No	Quarterly	2.0 (1.6-2.5)	П	N/A	Naturally present in the environment
Total THMs	μg/L	No	Quarterly		MCL = 80 Running	N/A	By-product of drinking water
Site 1				53 (25-54) <sup>1</sup>	Annual Average		chlorination.
Site 2				54 (33-58) <sup>1</sup>			
Site 3				50 (29-56) <sup>1</sup>			
Site 4				33 (18-42) <sup>1</sup>			
Site 5				50 (35-66) <sup>1</sup>			
Total HAA5	μg/L	No	Quarterly		MCL = 60 Running	N/A	By-product of drinking water
Site 1				15 (3.3-22) <sup>1</sup>	Annual Average		chlorination.
Site 2				13 (4.6-20) <sup>1</sup>			
Site 3				17 (11-20) <sup>1</sup>			
Site 4				15 (10-18) <sup>1</sup>			
Site 5				25 (16-29) <sup>1</sup>			
Chlorine Residual (POU)	mg/L	No	2024	0.55 (ND-1.46)	MRDL=4.0	4	Water additive used to control microbes.
Chlorine Dioxide Residual (EP)	mg/L	No	2024	0.050 (ND- 0.200)	MRDL= 0.8	0.8	Water additive used to control microbes.
Chlorite	mg/L	No	2024	0.414 (0.016- 0.445) <sup>2</sup>	MCL = 1.0	0.8	By-product of drinking water disinfection.

Inorganics							
Barium	mg/L	No	11/5/24	0.031	MCL=2	2	Drilling wastes; erosion of natural deposits.
Copper	mg/L	No	2023	0.140 (0.0096 -0.610)	AL=1.3	1.3	Household plumbing corrosion; erosion of natural deposits; wood preservatives.
Lead	μg/L	No	2023	8.8 (ND-17)	AL=15	0	Household plumbing corrosion; erosion of natural deposits.
Nitrate	mg/L	No	11/5/24	1.25	MCL=10	10	Fertilizer runoff; septic tank leaching; sewage; erosion of natural deposits.
Sodium	mg/L	No	11/5/24	34.4	See Water Quality, Section C	N/A	Naturally occurring; road salt; animal waste; water softeners; water treatment chemicals.
Unregulated Perfluoroalk	yl Substar	ices					
Perfluorobutanoic acid (PFBA)	ng/L	No	11/8/23	3.38	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Perfluoropentanoic acid (PFPeA)	ng/L	No	11/8/23	2.15	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Unregulated Contaminant	s (UCMR5	)					
Perfluorooctanoic acid (PFOA)	ng/L	No	2024	1.2 (1.0-1.4)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Perfluorooctanesulfonic acid (PFOS)	ng/L	No	2024	0.6 (ND-1.1)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Perfluorohexanoic acid (PFHxA)	ng/L	No	2024	1.3 (1.2-1.3)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Perfluorobutanoic acid (PFBA)	ng/L	No	2024	2.3 (1.6-2.7)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
Perfluoropentanoic acid (PFPeA)	ng/L	No	2024	1.6 (1.3-1.8)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.
1H, 1H, 2H, 2H- perfluorooctane sulfonic acid (6:2 FTS)	ng/L	No	2024	3.2 (ND-11.5)	Unregulated	N/A	Released into the environment from widespread use in commercial and industrial applications.

<sup>&</sup>lt;sup>1</sup>See "maximum level detected" below. Range of site in parentheses.

<sup>3</sup>Source Water

les <sup>4</sup>A

 $<sup>^{2}</sup>$ Chlorite is the average of 3 distribution samples taken monthly. Range of all samples in parenthesis.

<sup>&</sup>lt;sup>4</sup>Average of quarterly samples at 5 sites. Range of sites in parenthesis.

<sup>&</sup>lt;sup>5</sup>Maximum monthly average.

### Notes and Definitions for Table 3:

**AL (action level)**: The concentration of a contaminant that, if exceeded, triggers additional treatment or other requirements that a water system must follow.

**Lead and Copper**: The maximum level values reported for lead and copper represent the 90th percentile of the samples taken. A percentile is a value on a scale of 100 that indicates the percent of a distribution that is equal to or below it. The 90th percentile is equal to or greater than 90% of the lead and copper values detected at your water system.

The action level for lead was exceeded at one of the 30 sites tested. Testing for these metals is only required every three years.

HAA5 (haloacetic acids): These are a group of chemicals that are formed when chlorine or other disinfectants used to control microbial contaminants in drinking water react with naturally occurring organic and inorganic matter in water. The regulated haloacetic acids, known as HAA5, are monochloroacetic, dichloroacetic, trichloroacetic, monobromoacetic, and dibromoacetic acids. The maximum level detected of HAA5 is the highest of the four quarterly running annual averages calculated during the year and is the basis of the MCL for these compounds.

**Maximum Level Detected**: The highest measurement detected for the contaminant during the year. For total THMs and HAA5 the maximum level detected is the highest of the four quarterly running annual averages during the year.

**MCL** (maximum contaminant level): The highest level of a contaminant that is allowed in drinking water. MCLs are set as close to the MCLGs as feasible.

**MCLG (maximum contaminant level goal)**: The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs allow for a margin of safety.

mg/L (milligrams per liter): Corresponds to one part in one million parts of liquid (parts per million, ppm).

**MRDL** (maximum residual disinfection level): The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary to control microbial contaminants.

**MRDLG (maximum residual disinfectant level goal)**: The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contamination.

ng/L (nanograms per liter): Corresponds to one part of liquid to one trillion parts of liquid (parts per trillion-ppt).

N/A (not applicable).

**ND** (not detected): Laboratory analysis indicates that the constituent is not detectable.

**NTU** (nephelometric turbidity unit): A measure of the clarity of water. Turbidity of approximately 5 NTU is barely noticeable by the average person.

pCi/I (picocuries per liter): A measure of radioactivity in water.

Range: The range of lowest to highest measurements detected for contaminants measured during the year.

**THM (trihalomethanes)**: These are a group of chemicals that are formed when chlorine or other disinfectants used to control microbial contaminants in drinking water react with naturally occurring organic and inorganic matter in water. The regulated trihalomethanes are bromodichloromethane, bromoform, chloroform, and dibromochloromethane.

These compounds result from the disinfection of water with chlorine. The maximum level detected of THMs is the highest of the four quarterly running annual averages calculated during the year and is the basis of the MCL for these compounds.

TT (treatment technique): A required process intended to reduce the level of a contaminant in drinking water.

ug/L (micrograms per liter): Corresponds to one part in one billion parts of liquid (parts per billion, ppb).

### **F. Non-Detected Contaminants**

Table 4: Non-Detected Contaminates: Bolton Point Municipal Water System

CONTAMINANT	Sample Year
Microbiological	2024
E. Coli	Х
Inorganics	2024
Antimony	Х
Arsenic	Х
Beryllium	Х
Cadmium	Х
Chromium	Х
Cyanide,Total	Х
Fluoride	Х
Mercury	Х
Nickel	Х
Selenium	Х
Thallium	Х
Synthetic Organics &	2023
Pesticides	2023
Alachlor	Х
Aldicarb	Х
Aldicarb sulfone	Х
Aldicarb sulfoxide	Х
Atrazine	Х
Carbofuran	Х
Chlordane, Total	Х
1,2-Dibromo-3-	Х
chloropropane	^
1,2-Dibromoethane	Х
2,4-D	Х
Endrin	Х
Heptachlor	Х
Heptachlor epoxide	Х

Methoxychlor	х
PCB - aroclor 1016	х
PCB - aroclor 1221	х
PCB - aroclor 1232	Х
PCB - aroclor 1242	Х
PCB - aroclor 1248	Х
PCB - aroclor 1254	Х
PCB - aroclor 1260	Х
Pentachlorophenol	Х
Toxaphene	х
2,4,5-TP (Silvex)	Х
Aldrin	Х
Benzo(a)pyrene	Х
Butachlor	Х
Carbaryl	Х
Dalapon	Х
bis (2-ethylhexyl)	Х
adipate	^
bis (2-ethylhexyl)	x
pthalate	^
Dicamba	Х
Dieldrin	х
Dinoseb	Х
Hexachlorobenzene	Х
Hexachlorocyclopenta-	Х
diene	, ,
3-Hydroxycarbofuran	Х
Methomyl	х
Metolachlor	Х
Metribuzin	Х
Oxamyl (Vydate)	Х
Picloram	Х
Propachlor	Х

Simazine	Х
Principal Organics, Vi-	2024
nyl Chloride, and MTBE	
Benzene	Х
Bromobenzene	Х
Bromochloromethane	Х
Bromomethane	Х
n-Butylbenzene	Х
sec-Butylbenzene	Х
tert-Butylbenzene	Х
Carbon tetrachloride	Χ
Chlorobenzene	Х
Chloroethane	Χ
Chloromethane	Х
2-Chlorotoluene	Χ
4-Chlorotoluene	Χ
Dibromomethane	Х
1,2-Dichlorobenzene	х
1,3-Dichlorobenzene	Х
1,4-Dichlorobenzene	Х
Dichlorodifluoro- methane	х
1,1-Dichloroethane	X
1,2-Dichloroethane	X
1,1-Dichloroethene	X
cis-1,2-Dichloroethene	X
trans-1,2-	Х
Dichloroethene	٨
1,2-Dichloropropane	Χ
1,3-Dichloropropane	Χ
2,2-Dichloropropane	Χ
1,1-Dichloropropene	Χ
cis-1,3- Dichloropropene	Х

·	
trans-1,3-	х
Dichloropropene	
Ethylbenzene	Х
Hexachlorobutadiene	Х
Isopropylbenzene	Х
p-Isopropyltoluene	Х
Methylene chloride	Х
n-Propylbenzene	Х
Styrene	х
1,1,1,2-	v
Tetrachloroethane	Х
1,1,2,2-	Х
Tetrachloroethane	^
Tetrachloroethene	Х
Toluene	Х
1,2,3-Trichlorobenzene	Х
1,2,4-Trichlorobenzene	х
1,1,1-Trichloroethane	х
1,1,2-Trichloroethane	Х
Trichloroethene	Х
Trichlorofluoromethane	х
1,2,3-Trichloropropane	Х
1,2,4-Trimethylbenzene	х
1,3,5-Trimethylbenzene	х
m-Xylene	Х
o-Xylene	Х
p-Xylene	Х
Vinyl chloride	х
MTBE	х
Radiological	2023
Gross Alpha	х
Radium-226	х
Radium-228	X
1,4-Dioxane/PFAS	2023
1,4-Dioxane	X
Perfluorooctanoic Acid	] - ·
(PFOA)	Х
Perfluorooctane	
sulfonate (PFOS)	Х
·	

Unregulated Contami- nants (UCMR5)	2024
Lithium	Х
Perfluoroheptanoic	X
acid (PFHpA)	^
Perfluorononanoic acid	Х
(PFNA)	^
Perfluorodecanoic acid (PFDA)	Х
Perfluoroundecanoic acid (PFUnA)	Х
Perfluorododecanoic acid (PFDoA)	Х
Perfluorobutanesul- fonic acid (PFBS)	Х
Perfluorohexanesul-	X
fonic acid (PFHxS)	^
Hexafluoropropylene	Х
oxide dimer acid (HFPO	
-DA) (Gen X chemicals)	
Perfluoroheptanesul-	Х
fonic acid (PFHpS)	
Perfluoropentanesul-	Х
fonic acid (PFPeS)	
1H, 1H, 2H, 2H-	Х
perfluorodecane sul-	
fonic acid (8:2 FTS)	
9-	Х
chlorohexadecafluoro-	
3-oxanone-1-sulfonic	
acid (9Cl-PF3ONS)	
11-chloroeicosafluoro-	Х
3-oxaundecane-1-	
sulfonic acid (11Cl-	
PF3OudS)	
1H, 1H, 2H, 2H-	Х
perfluorohexane sul-	
fonic acid (4:2 FTS)	
Nonafluoro-3,6-	Х
dioxaheptanoic acid	
(NFDHA)	
Perfluoro(2-	Χ
ethoxyethane)sulfonic	
acid (PFEESA)	

_	
Perfluoro-3- methoxypropanoic acid	Х
Perfluoro-4-methoxybutanoic acid (PFMOBA)	Х
Perfluorotridecanoic acid (PFTrDA)	Х
Perfluorotetradecanoic acid (PFTDA)	Х
n-ethyl perfluorooctanesul- fonamidoacetic acid	Х
n-methyl perfluorooctanesul- fonamidoacetic acid	Х

### G. Major Modifications Completed in 2024

### **Water Main Projects**

Graham Road and Dart Drive 5800' water main replacement. (Village of Lansing)

### **System Improvements**

Emergency generator installation at the Coddington and Troy Road Pump Stations. (Town of Ithaca)

### Treatment Plant (Bolton Point)

• Initial phase of the electrical upgrade project.

### H. Future Projects and Capital Improvements (Planned for 2025)

### Water Main Projects

• Dryden Road 8500' water main replacement. (Town of Dryden)

### **System Improvements**

- Installation of emergency generator at the Village Circle Pump Station (Town of Lansing)
- Installation of new pumps at the Brown Road Pump Station (Village of Lansing)

### Treatment Plant (Bolton Point)

• Treatment plant electrical upgrades, final phase.

### I. Water Conservation Measures

You can play a role in conserving water by becoming conscious of the amount of water your household is using and by looking for ways to use less whenever you can. It is not hard to conserve water. The following are some ideas that you can apply directly in your own home.

Use your water meter to detect hidden leaks. Turn off all taps and water using appliances, then record the meter reading and check the meter after 15 minutes. If it registers, you have a leak.

Restaurants in the U.S. serve approximately 70 million meals a day. Every glass of water brought to your table requires another two glasses of water to wash and rinse the glass.

The bathroom accounts for 75 percent of the water used inside the home.

Water your lawn only when it needs it. If you step on the grass and it springs back up when you move, it doesn't need water. If it stays flat, it does.

Put 10 drops of food coloring in your toilet tank. If the color shows up in the bowl without flushing, you have a leak to repair. It is common to lose up to 100 gallons a day from a toilet leak. Fix it, and you save more than 30,000 gallons a year.

Do not hose down your driveway or sidewalk. Use a broom to clean leaves and other debris from these areas. Using a hose to clean a driveway can waste hundreds of gallons of water.

If every American home installed low-flow faucet aerators, the United States would save 250 million gallons of water a day.

Fix leaks as soon as they are found. A dripping faucet with a 1/16 inch stream wastes 100 gallons of water per day.

Saving water can lower your power bills by reducing your demand for hot or pumped water. These few simple steps will preserve the resource for future generations and also save up to 30% on your bill.

### J. Security Concerns

Generally, security threats to our water system have consisted of primarily minor vandalism and property damage. However, our security efforts focus to a high degree on the much less likely, but more serious, threat of intentional contamination of the water supply. We have performed security assessments of our entire system and updated our Emergency Response Plans to cover the possibility of terrorism. Weaknesses in procedures have been corrected and improvements to increase the security of the infrastructure have been undertaken. Local police are aware of the security needs of the water systems and have maintained increased patrolling of the facilities.

Your awareness and reporting of suspicious activity throughout the system is appreciated. The Bolton Point Water Supply Emergency Plan was updated and sent for approval by the NYSDoH in 2023. A copy of the public version is available for viewing at the Bolton Point water treatment plant, 1402 East Shore Drive, Ithaca New York, 14850, or by contacting Glenn Ratajczak, Production Manager, 277-0660, ext. 241, gratajczak@ boltonpoint.org

### K. Source Water Protection

The New York State Health Department is in the process of developing a Source Water Assessment Report for every surface drinking water source in the state. When the report for our source is completed, we will review it and provide a summary. If this report becomes available in 2025, a summary will be posted on our website and provided in next year's Annual Drinking Water Quality Report.

# L. Lead Service Line Inventory

A Lead Service Line (LSL) is defined as any portion of pipe that is made of lead which connects the water main to the building inlet. A LSL may be owned by the water system, owned by the property owner, or both. The inventory includes both potable and non-potable SLs within a system. In accordance with the federal Lead and Copper Rule Revisions (LCRR) our system has prepared a lead service line inventory and have made it publicly accessible by contacting Glenn Ratajczak at 277-0660 ext 241 or visiting our website at boltonpoint.org

# HIGH QUALITY DRINKING WATER FOR TOMPKINS COUNTY RESIDENTS

## **CURRENT RESIDENT**

### Water Trivia

- There are over 58,900 community water systems in the United States processing more than 34 billion gallons per day.
- The average residence in the United States uses 107,000 gallons of water a year.
- It takes 62,600 gallons of water to produce one ton of steel.
- Eighty percent of the earth's surface is covered by water, but only one percent of the earth's water is suitable for drinking.
- It takes 101 gallons of water to make one pound of wool or cotton.
- Water acts as a natural buffer against extreme or rapid changes in the earth's temperature.
- It would take 219 million gallons of water to cover one square mile with one foot of water.
- One gallon of water weighs 8.34 pounds.
- When the weather is very cold outside, let the cold water drip from the faucet served by exposed pipes. Running water through the pipe
   even at a trickle helps prevent pipes from freezing.

### Resources

Web sites with more water information and activities for children

- www.epa.gov/safewater/index.html
- www.epa.gov/safewater/kids/index.html